

E Series

A horizontal bar with a yellow segment on the left, a green segment in the middle, and a black segment on the right.

The **DBX** three-slot system involves deep under-seed cultivation, a shallow bed of seed, a defined “slot” trench for water harvesting and a protective environment for germinating seeds.

Since the introduction to the market in 1994 the **DBX** precision seeding system for broadacre farming has consistently led the way in terms of precision seed placement and under-seed cultivation.

The system is unique in that it has been developed for both winter and summer cropping and is suitable for all soil types. Its design ensures seeding accuracy with excellent subsoil cultivation and minimal topsoil disturbance. Each season, you can visibly see improvements in soil structure and quality and water infiltration will significantly increase.

The **DBX** has been designed to overcome the problems of poor depth penetration, inadequate seed placement and incorrectly placed seed. Its reliability, performance and proven higher yields are features that will continue to set it apart from others in the market.

By using the **DBX** system, you can be confident of:

- Increased productivity gains
- Improved yields
- Early vigour and growth
- Higher soil nutrient quality
- Less water usage



E Series

Our **DBX E Series** is available in 9 models, each with dual wheels on the centre section and fold up wings. High flotation 400/55x22.5 wheels are standard on all models. Each model is available in either 260mm or 300mm row spacing. The centre section consists of 22 tines for the 260mm row spacing and 19 tines for the 300mm machines. These planters are the largest in the range built for extremely extensive cropping areas.

The **E Series** can be combined with all airseeder models in the **DBX Stream** range.

Model	No of Tines	Cut Width	Power KW/Hp	Transport Width	Transport Height
48-260E	48	14.48	251 / 336	7.42	4.61
54-260E	54	14.04	282 / 378	7.42	5.35
60-260E/df	60	15.60	313 / 420	7.42	5.03
64-260E/df	64	16.64	334 / 448	7.42	5.03
70-260E/df	70	18.20	366 / 490	7.42	5.03
43-300E	43	12.90	244 / 301	7.37	4.63
49-300E	49	14.70	256 / 343	7.37	5.60
55-300E/df	55	16.50	287 / 385	7.96	4.69
61-300E/df	61	18.30	318 / 427	7.96	5.59

- Tine type: Hydraulic edge-on high breakout cushion return.
- Specifications are nominal and subject to change.
- Dimensions and power requirements are nominal and based on machines with standard 180mm (7") blades.
- Transport height and width may exceed local limits and all machines are towed at owner's risk.
- Options available:
 - Coulters

