

# T Series

A horizontal bar with a yellow segment, a green segment, and a black segment, positioned below the 'T Series' text.

The **DBX** three-slot system involves deep under-seed cultivation, a shallow bed of seed, a defined “slot” trench for water harvesting and a protective environment for germinating seeds.

Since the introduction to the market in 1994 the **DBX** precision seeding system for broadacre farming has consistently led the way in terms of precision seed placement and under-seed cultivation.

The system is unique in that it has been developed for both winter and summer cropping and is suitable for all soil types. Its design ensures seeding accuracy with excellent subsoil cultivation and minimal topsoil disturbance. Each season, you can visibly see improvements in soil structure and quality and water infiltration will significantly increase.

The **DBX** has been designed to overcome the problems of poor depth penetration, inadequate seed placement and incorrectly placed seed. Its reliability, performance and proven higher yields are features that will continue to set it apart from others in the market.

By using the **DBX** system, you can be confident of:

- Increased productivity gains
- Improved yields
- Early vigour and growth
- Higher soil nutrient quality
- Less water usage



# T Series

Our **DEX T Series** is available in three models, each with dual wheels on the centre section and fold up wings. Each model is available in either 260mm or 300mm row spacings. The centre section consists of 11 tines, which makes this the smallest machine in the range.

The **T Series** is combined with the T-model Xtreams due to flotation considerations. The options for adding coulters, as well as a spray system for pre-emergent control of weeds, are available.

Model	No of Tines	Cut Width	Power KW/Hp	Transport Width	Transport Height
21-260T	21	5.46	110 / 147	4.56	2.6
23-260T	23	5.98	120 / 160	4.56	2.9
25-260T	25	6.5	140 / 175	4.56	3.2
21-300T	21	6.3	110 / 147	5.0	2.8
23-300T	23	6.9	120 / 160	5.0	3.1
25-300T	25	7.5	140 / 175	5.0	3.4

- Tine type: Hydraulic edge-on high breakout cushion return.
- Specifications are nominal and subject to change.
- Dimensions and power requirements are nominal and based on machines with standard 180mm (7") blades.
- Transport height and width may exceed local limits and all machines are towed at owner's risk.
- Options available:
  - Coulters



P.O. Box 334 Albertinia, 6695, South Africa  
t: +27 28 735 2425 | f: +27 28 735 2424  
e: x@xfarm.co.za | w: www.xfarm.co.za